



FOR IMMEDIATE RELEASE

NAB 2015, BOOTH C5409

CLEAR-COM TO SHOW LQ INTERCOM CONNECTIVITY SOLUTION AT NAB 2015

ALAMEDA, USA – MARCH 10, 2015 — [Clear-Com](#)® will show its recently released **LQ™ Series**, IP interface devices designed for linking intercom and audio systems across long distances over IP networks at this year's NAB Booth C5409. With LQ devices, users of 2-wire partyline intercoms and 4-wire intercom and audio systems would be able to cost-effectively and quickly expand their intercom systems with no additional wiring. All the intercom linking is achieved over IP networks: house LAN, WAN or internet. NAB 2015 takes place at the Las Vegas Convention Center (LVCC) from April 13-16, 2015.

Released in January 2015, the LQ Series is Clear-Com's newest line of Intercom Connectivity (ICON) solutions. With either the two-wire (LQ-2W2) or four-wire (LQ-4W2) options, the LQ devices are ideal for intercom users who need to cost-effectively extend their existing intercom systems to single or multiple remote locations over their IT infrastructures, eliminating lengthy audio cable runs. LQ can also interface between different intercom systems routing both call signaling and audio over LAN, WAN or Internet IP connections: 2-wire partyline with other OEM partyline systems, 2-wire with 4-wire devices, and 4-wire with 4-wire systems. The LQ-2W2 is both Clear-Com and RTS TW compatible. A maximum of six LQ Series interfaces can be linked together to form a managed network.

“Regardless of the type of intercom system being used, the LQ Series makes it easy to extend the system to the other side of a building, across campus, or across the world,” said Stephen Sandford Clear-Com’s Product Manager for Matrix and IP interfaces. “The ability to have an intercom station wherever Internet access is available is invaluable as productions become more complex and the need for reliable distributed communications becomes more important. The LQ Series addresses this need perfectly.”

These two-channel devices are light-weight, portable and compact. They are easy to deploy and do not take up valuable rack space. Configuration is effortlessly achieved over a browser based user interface. Unique features of the LQ Series devices include Power over Ethernet,

(more)

auto-nulling capability, multi-cast 1 to 5 routing, auto-discovery and use of the OPUS codec for high quality audio and low bit rate transmission.

The complete Clear-Com line of new and enhanced products will be available for demonstration at NAB 2015 on Booth C5409.

###

About Clear-Com®

Clear-Com, an HME company, is a trusted global provider of professional real-time communications solutions and services since 1968. We innovate market proven technologies that link people together through wired and wireless systems.

Clear-Com was first to market portable wired and wireless intercom systems for live performances. Since then, our history of technological advancements and innovations has delivered significant improvements to the way people collaborate in professional settings where real-time communication matters. For the markets we serve -- broadcast, live performance, live events, sports, military, aerospace and government-- our communication products have consistently met the demands for high quality audio, reliability, scalability and low latency, while addressing communication requirements of varying size and complexity. Our reputation in the industry is not only based on our product achievements, but also on our consistent level of customer engagement and dedication to delivering the right solutions for specialized applications, with the expertise to make it work. Around the globe and across markets, Clear-Com's innovations and solutions have received numerous awards and recognitions for ingenuity and impact to customers.

For more information, please visit www.clearcom.com.

Media Contact(s):

Denise Williams
Publicist
denise@bubblesqueak.co.uk
+1.503.806.0755

Judy Cheng
Director, Worldwide Marketing
Judy.Cheng@Clearcom.com
+1.510.337.6600 (not for publication)